

Glasshouse Theatre

Technical Specifications

Commented [DP1]: Updated 28/02/23

The information contained in this document is accurate at the date specified above. To ensure information is up to date please contact the venue closer to the date of your intended event.

















CONTENTS

STAGE 4
Brief Stage Description
Stage Dimensions
AUDITORIUM5
Overview:5
Removable Seats:
Capacity: 5
ORCHESTRA PIT / FORESTAGE EXTENSION
SMOKE STOP CURTAIN
FLYING SYSTEM6
Overview: 6
Fly System Details 6
STAGING8
Drapery8
Access Equipment:
Staging Units:
Stage Covers:
Stage Floor:
Rigging / Staging Equipment
VEHICLE ACCESS
Loading Dock Access
Restrictions / Obstructions
Loading Dock Dimensions
Scenery Access to Stage
LIGHTING
Positions
Control
Control Position
Dimming
House Lights
Power
Cabling
AUDIO
Control Positions















Control	16
Speakers & Amplification	16
Playback	16
Microphones – Radio	17
House frequencies (theatre)	17
Accessories	17
Line Patching	17
Cabling	18
Audio Notes	18
AUDIO VISUAL	19
Projectors	19
Screens	19
AV Equipment	19
Cabling	19
BACKSTAGE	21
Communications	21
Dressing Rooms	22
Laundry / Wardrobe	22
Production Management Facilities	22
Greenroom	22
Stage Door	22
ADDITIONAL INFORMATION	23
Orchestral	23
Rehearsal Spaces	23
Other	23
Staff / Scheduling Requirements	23
VENUE	24
Venue Address	24
Postal Address	24
	2.4













STAGE

Brief Stage Description

- Stage is Not raked
- Stage is 920mm above Floor of 'A' Row.
- Stage Crossover behind rear wall of stage.
- Stage Surface is 6mm Masonite on top of 2 x 19mm Ply
- Stage Uniformly distributed load limit = 5.5kpa
- Stage point load limit = 5.5KN
- Smoke curtain is in front of proscenium and does not drop to stage level

Stage Dimensions

Proscenium Arch:

- Width is 14'000mm (Fabric Tormentors can reduce width to 10m)
- Height is
 - 9880mm from Stage floor to underside of concrete
 - 9348mm from stage floor to underside of acoustic shell
- Thickness of proscenium arch is 200mm

Distance From:

SL = Setting Line (upstage edge of proscenium)

CL = Centre Line

- SL to DS edge of apron = **900mm**
- SL to DS edge of Orchestra Lift/Pit = 3700mm at CL (Curved pit)
- SL to first fly line = **520mm** (House Curtain)
- SL to last upstage fly line = **8420mm** (Line 25)
- SL to rear wall = 10'000mm
- CL to OP wall = 9400mm
- CL to PS wall = 9400mm
- Stage floor to underside of grid 16'000mm

Overhead obstructions:

- Air conditioning ducts OP & PS walls at a height of 7000mm above stage level
- Catwalks (fly floor / patch floor) 8100mm above stage level













AUDITORIUM

Overview:

The Glasshouse Auditorium is 594 tiered fold down seats, including a Balcony. Removable treads from stage to auditorium are available upon request and require the removal of seating. Wheel chair spaces are available in both balcony and stalls, and requires the removal of seating to accommodate.

Removable Seats:


- Orchestra Pit = **41 seats** (A9 A24 & B4 B28)
- Treads = 6 seats (OP side B4, B5, C4 & P Side B27, B28, C29)
- Wheel Chair Seating = 12 seats accommodates 8 wheelchairs

Capacity:

- Full Theatre = 594
 - Stalls = 403
 - Balcony= 191
- Full Theatre with Orchestra Pit / Forestage = 541
 - Stalls = 356
- Balcony = 191

 Full Theatre with Treads (both sides) = 582
 - Stalls = 397
 - Balcony = 191





STALLS BOXES DRESS CIRCLE















ORCHESTRA PIT / FORESTAGE EXTENSION

- Orchestra pit / Forestage extension is a Serapid[™] Lift system
- Orchestra pit / Forestage extension is semi-circular
- Orchestra pit / Forestage extension can be set anywhere between stage level and 3000mm below stage level
- Uniform distributed load = 7.5 kPa
- Maximum point load = 4.5 kN
- Static load limit = 10'000kgs
- Working load limit (dynamic) = 6000kgs
- Dimensions = 8300mm width x 2200mm depth @ centre
- Orchestra Pit capacity = 20 persons

SMOKE STOP CURTAIN

Smoke Stop Curtain is located **DS of Proscenium**. It is an automatic drop down curtain triggered by fire / smoke in the fly tower. The smoke curtain drops from above the proscenium, to a height of 5000mm above stage level. It is designed to change the flow of smoke, not to create a solid barrier between the stage and the auditorium.

FLYING SYSTEM

Overview:

The Glasshouse Theatre's Flying System consists of 26 motor winches of which 25 are controlled via a 'Siemens' control dongle. The system can program up to 10 presets. Presets cannot be played back simultaneously.

The House curtain (line 1) can be controlled via a separate push button controller located mid-stage prompt.

Fly System Details:

- Can be operated from multiple positions:
 - Stage level prompt side (preferred for load in / out)
 - Stage level OP side
 - Fly floor OP side (preferred position for performance)
 - Fly floor PS
 - Motor winch room (for maintenance)
- Number of lines controlled via Dongle = 25 (header is manual control only)
- Batten Drift = 15'400mm
- Batten Type = RHS Steel 75mm x 50mm
- Batten Length = 14'500mm
- Batten extensions = 4 available adding ½ metre per side
- Batten Pick-ups = 5 pickups (1 at centre then at 2900mm increments)
- Batten Point load = 200kg
- Batten W.L.L> = 400kg
- All fly bars can be swung (including LX bars)

SEE HANGING PLOT FOR LINE ALLOCATIONS AND FURTHER INFO













Current Standard Hanging Plot 20/09/2017

Line type: MW= Motor Winch

Show:

Line#	Distance	Line	W.L.L	CURRENT	PROPOSED	OTHER
	from SL	Type	Stripped	VENUE	VENUE	INFORMATION
		/1-		HANGING PLOT	HANGING	
					PLOT	
-	260mm	MW	1000KG	TEASER	N/A	
1	520mm	MW	400KG	House		
				Curtain		
2	720mm	MW	400KG	Tormentors		
3	920mm	MW	400KG	LX Bar 1		
4	1620	MW	400KG			
5	1820	MW	400KG			
6	2020	MW	400KG			
7	2220	MW	400KG	Border 1		
8	2420	MW	400KG	Legs 1 (with 400mm return)		
9	2620	MW	400KG			
10	2820	MW	400KG			
11	3020	MW	400KG	LX Bar 2		
12	3220	MW	400KG			
13	3620	MW	400KG	Border 2		
14	4020	MW	400KG	Legs 2 (With1000mm return)		
15	4420	MW	400KG	LX Bar 2a		
16	4820	MW	400KG	Border		
17	5220	MW	400KG	Black Tabs		
	<u> </u>			Diagram 1 and		
18	5620	MW	400KG	LX Bar 3		
19	6020	MW	400KG	Legs 3 (With1000mm return)		
20	6420	MW	400KG	Border		
21	6820	MW	400KG	LX bar 4		
	-					
22	7220	MW	400KG	Legs 4		
				- 3		
23	7620	MW	400KG	LX bar 5		
24	8020	MW	400KG	Black Tabs		
	- -					
25	8420	MW	400KG	Cyclorama		
				,	l	













STAGING

Drapery

*Type	Material	Colour	Width	Drop	Qty
House Curtain	Satin (100%fullness)	Charcoal	8100mm	7500mm	2 (1 Pair)
Borders	Wool (0%fullness)	Black	15000mm	4000mm	5
Legs	Wool (0%fullness)	Black	4000mm	9000mm	10 (5 pairs)
Tabs / Smother	Wool (50%fullness)	Black	7800mm	7000mm	4 (2 Pairs)
Cyclorama	Filled Cloth	White	15000mm	7000mm	1
Gauze	Filled Cloth	Black	15000mm	7000mm	1
Borders (not in use)	Wool (50%fullness)	Black	15000mm	3000mm	5
Legs (not in use)	Wool (50%fullness)	Black	3000mm	7000mm	8 (4 pairs)
Legs (not in use)	Wool (50%fullness)	Black	2000mm	7000mm	4 (2 pairs)

Access Equipment:

- Elevated Work Platform:
 - Genie GR20 Single man EWP. Maximum height is 6m (20ft)
- Ladders:
 - o 2 of 2.4m Step ladder Fibreglass
 - 2 of 1.2m Step ladder Fibreglass
 - o 1 of 3.3m to 5.8m Extension Ladder Aluminium

Staging Units:

- Mega-Deck 1.2m x 2.4m x 10 units
 - o Heights @ 300mm / 600mm / 900mm

Stage Covers:

• Harlequin Cascade Dance Floor, 5 pieces each 2m wide x 14m long, laid across stage.

Stage Floor:

All penetrations into stage floor must be approved by the Glasshouse prior to arrival and will be at cost to the presenter. Screwing to the Stage floor is allowed to a MAXIMUM DEPTH OF 35MM'

Rigging / Staging Equipment

Item	Detail / Accessories	W.L.L.	Qty
Chain Blocks		500kg	1
Shackles	D - Shackles	1t	30
Shackles	Bow - Shackles	0.5t	125
Shackles	Bow - Shackles	0.75t	5
Shackles	Bow - Shackles	1t	19
Shackles	Bow - Shackles	2t	10
Shackles	Bow - Shackles	3.25t	3
Shackles	Bow - Shackles	6.5t	20
Turnbuckles	200mm Stainless	100kg	16
Turnbuckles	300mm	100kg	40
Girder Clamps		2t	4
FSWR	8m – Black Sheath	80kg	10
FSWR	6m – Black Sheath	80kg	9
FSWR	4m – Black Sheath	80kg	4
FSWR	2m – Black Sheath	80kg	4
FSWR	1m	80kg	6
Scaffold coupler	90deg Fixed		24
Scaffold coupler	Swivel		3
Sling	"yuppie Strap" 1/2m flat with buckles	100kg	23
Sling	1/2m Flat sling with Rings	100kg	23













Sling	1m Black Round	1t	9
Sling	2m Black Round	1t	2
Sling	1m Green Flat Webb	2t	3
Sling	2m Green Flat Webb	2t	2
Shot Bags	Black	10kg	30
Iron Counterweight	(owned by Jands – Not always on site)	12kg	40

All overhead elements must be rigged with rated equipment and fitted and installed by qualified personnel. Rigging Ticket must be presented to glasshouse management prior to rigging work commencing.













VEHICLE ACCESS

Loading Dock Access

Access to the Glasshouse loading dock is through the Hay Street Road Enclosure (via Clarence Street)

Vehicles must manoeuvre through pedestrian walkways to access the loading dock and as such it is essential the following restrictions are observed:

Restrictions / Obstructions

- Trucks shall enter and leave the Hay Street Road Enclosure and Glasshouse loading dock under direction and supervision of Glasshouse traffic controllers.
- The Glasshouse must be notified a minimum of 10 business days prior to arrival
 of all heavy vehicles requiring access to loading dock...
- Glasshouse staff will be scheduled accordingly to assist in the implementation of the Traffic Management Plan required to facilitate access.
- Trucks exceeding 8 tonne or 8 metres in length are prohibited from leaving the site via streets to the west of Hay Street, north of Clarence Street and north of Gordon Street.
- No vehicle exceeding the dimension of a 19m long articulated will be allowed to attend the site

Loading Dock Dimensions

- Loading Dock Height above ground level = 925mm
- Loading Dock Clearance Height = 4495mm
- Dock Leveller heights
 - 700mm Minimum operating height above ground level
 - 1500mm Maximum operating height above ground level
- Dock Door / to scenery dock Dimensions:
 - **3410mm** High
 - 3250mm Wide
 - 4710mm Diagonal

Scenery Access to Stage:

- Direct from scene dock sliding acoustic door
 - **5900mm** High
 - 4000mm Wide
 - 7128mm Diagonal
- BOH Lift to Dressing Rooms / Laundry
 - 2800mm Door Height
 - 2000mm Door Width
 - 3000mm Internal Lift Dept
 - 3400mm Internal Lift Height













LIGHTING

Positions

- Overhead LX Bars
 - 6 bars each comprising of 4 sections of Jands JLX lighting bars
 - Bar width = 14'000mm
 - No of outlets per bar = 24
 - See hanging plot for current positions
- FOH Bridge # 1
 - Distance from setting line = 14'900mm @ 55°
 - Bar Width = 19'000mm
 - No of outlets = 24
- FOH Bridge # 2
 - Distance from setting line = 18'200mm @ 40°
 - Bar Width = 17'000mm
 - No of outlets = 48
 - Standard follow spot positions @ 5m from centre PS & OP. Centre is also available by request.
- Circle Rail
 - Distance from setting line = 11'500mm
 - Bar Width = 9'000mm
 - No of outlets = 10
 - Bar is Curved Access via extension ladder in Auditorium
- Balcony bars (OP & PS)
 - Distance from setting line = 3'000mm (stage end) / 6000mm (Rear auditorium end)
 - Bar Width = 3'000mm
 - No of outlets = 6 per side (12)
 - Bar is Curved Access via extension or A frame ladder in Auditorium
- FOH Box Booms (OP & PS)
 - Distance from setting line = 1000mm
 - Bar Width = 3'000mm
 - No of outlets = 12 per side (24)
 - Box Booms are dual bars split into 3 levels (4 outlets per level)
 - Stage (900, 2000) Mid (4100, 4700) Upper (6800, 7300)

Control

- Lighting desk is an ETC lon
- Lighting desk has 6000 Control channels
- Lighting desk has 6 DMX outputs (2 Via Local, 4 Via Cat5 ETC DMX Node)
- DMX is distributed by 3 Jands DD-8 splitters and 1 LCS Delta splitter (Not RDM Capable)
- Lighting desk has wireless remote 'riggers' control via an iPad with ETC Software.

Control Position

- Control Room located at rear of Stalls behind glass sliding panels
- Middle of Stalls for Pre Production (Temporary Production Desk)
- Side Stage and other various Locations Via Cat5 DMX Node

Dimming

- Total Dimmers = 318
 - Jands HPX Theatre 2.4kw = 144
 - Jands HPC 2.4kw = 24
 - Jands HPX Pro 5kw = 30
 - State Automation Solution Cool 2.4kw = 120

State Automation dimmers can be bypassed to allow 240v 'gpo' scenario – (physical bypass which removes DMX control from outlet)













THE ROSS FAMILY



House Lights

House lights are controlled via Dynalite control system. Dynalite control panels are located at prompt side of stage and control room. Different intensity presets are available however fade times are not adjustable from Dynalite control panels. See ##NB##

Power

- 3 Phase Outlets:
 - Stage Catwalks = 10 x 32a (used for lighting dimmers)
 - Above forestage (in FOH Rigging area) = 1 x 32a tech earth
 - FOH Bridge # 2 = 2 x 40a (OP) 1 x 32a (centre)
 - On stage = 2 x 40a (USOP & USPS) 1 x 32a tech earth (PS)
 - Stage Crossover = 1 x 32a tech earth (centre)
 - Under stage = 2 x 40a (USOP & USPS)
 - Loading Dock = 2 x 40a tech earth, 1 x 40a
 - Scene Dock = 2 x 32a
 - Fly Grid = 2 x 40a
- 240v 10a power outlets are available on stage
- Tech earth power is denoted by a green outlet

Cabling

- 240v Extension Cable:
 - Available in Various lengths and Quantities
- 3 phase Extensions:
 - 1 of 32amp x 10m length
 - 2 of 40amp x 15m length
 - 2 of 40amp x 10m length

Luminaries

Profiles:

Make	Model	Angle	Detail / Accessories	Watt	Qty
ETC	Source 4	5°	•	750w	2
ETC	Source 4	10°		750w	6
ETC	Source 4	14°		750w	18
ETC	Source 4	19°		750w	10
ETC	Source 4	26°		750w	9
ETC	Source 4 Zoom	15°-30°		750w	12
ETC	Source 4 Junior	25°-50°		575w	33
Selecon	Pacific Zoom	23°-50°		600w	13
Selecon	Pacific Zoom	14° - 35°		600w	22
Selecon	Pacific Zoom	45° - 75°		600w	2

Fresnels:

Make	Model	Angle	Detail / Accessories	Watt	Qty
Selecon	Rama	7°-50°	All with Barn doors	1200	28
Selecon	Arena	7°-60°	All with Barn doors	2000	10
Selecon	Acclaim		All with Barn doors	650	16

PCs:

Make	Model	Angle	Detail / Accessories	Watt	Qty
Selecon	Rama	5°-60°	All with Barn doors	1200	28

Floods / Washes:

Make	Model	Angle	Detail / Accessories	Watt	Qt	v















ETC	S4 - Par	Lens avail – VNS,NS, MFL, WFL	Aluminium Reflector	750w	52
Selecon	Aurora 4 cell		4 compartment Cyc Flood - Linear	1200w per cell	8
Chauvet	Parhex 12 RGBAW LED	Flood			12

Follow Spots:

. onon opers	•				
Make	Model	Angle	Detail / Accessories	Watt	Qty
Lycian	SuperArc 400 Model 1266		7 colour magazine Manual Dimmer Full closing Iris and Shutter	400	2

Additional Items:

Item	Make	Size	Detail / Accessories	Qty
Booms	Alloy Pipe	Various	Painted Black	
Boom Trolleys	Mobile on castors		Painted Black	10

Moving Lights:

Item	Make	Model	Detail / Accessories	Qty
LED Wash	Martin	Mac Aura	19 x 10w RGB array	20
LED Profile	Martin	Rush MH1	180w output	16
LED Profile	EK	E1	400w RGBW	8

Lighting Notes
OP and PS Balcony Masks DS edges of Apron from Bridge positions

Be aware that due to FOH 1 Position Focusing may cause issues with Low Fly Batten Deads

House Lights are Controllable Via DMX through the "House Lighting Desk Only" this takes up the 4^{th} Universe of DMX

The House Desk can be placed beside the touring console with the House lights controlled on a Fader.

The W.L.L. of the LX Bars with the standard 4 x Jands JLX Pro Bars = 150kg



















Page | 15

AUDIO

Control Positions

- In-Auditorium Mix position Located centre of row O (7 seats).
- Control Room at rear of Auditorium stalls behind sliding glass panels.
 NB Control Room is approximately 5db quieter than auditorium, and not recommended for mixing live, but preferred AV and lighting control position.

Control

- **Primary Mixer**
- Digico SD8 Digital Mixing desk, 60 mono or stereo input, 24 mono or stereo output busses, 12x12 matrix, 12 Control Group/VCA, Dual MADI I/O, UB MADI 48in/48out multi-track recording capabilities, with built in graphic EQ, effects/dynamics such as reverb, delay, and gates.
- Secondary Mixer (Monitor console and B/U for FOH, and subject to availability)
- **Digico SD11** Digital Mixing desk, 48 Input channels with 16/8 Local I/O, 24 mono or stereo output busses, 8x8 Matrix, 8 Control Group/VCA, with built in graphic EQ, effects/dynamics such as reverb, delay, and gates.
- Additional Effects Units available:
 - TC Electronic M-One reverb
 - TC Electronic D-Two delay

Speakers & Amplification

- · FOH Speakers:
 - 12 of JBL VRX LA 932 series (4 left, 4 centre, 4 right)
 - 2 of ASB 6128 Subs (hung behind centre speakers)
 - 2 of RCF HD 12-A MK4
 - 2 of SUB 705AS II (additional under balcony fill, 1 speaker and sub each side of stage)
- **FOH Amplification**
 - 5 of Crown XTI 6002
- Foldback Wedges:
 - 4 of Yamaha IF2208 (flown side fill, PS and OP approx. 1200mm and 4600mm from setting line)
 - 8 of Yamaha IF2208 (low profile floor foldback)
 - 6 of JBL PRX 512m
 - 2 of RCF HD 12-A MK4
 - 2 of EV SX300a
 - 2 of EV ZAx1

Playback

Item	Model	Detail / Accessories	Qty
CD Player	Denon DN360	Single CD Player with "auto- pause"	2
DI for PC/iPod playback	Radial Pro-AV2	Passive DI Box	2

Microphones and DI's













Item Make		Model	Detail / Accessories	Qty	
Vocal	Shure	Beta 58a		10	
Instrument	Shure	Beta 57a		2	
Vocal	Shure	Beta 87a		4	
Vocal	Shure	SM 58		2	
Instrument	Shure	SM 57		4	
Instrument	Shure	KSM27	Lge diaphragm condenser	2	
Instrument	Shure	PG 52	Kick drum mic	1	
Instrument	Shure	PG 56	Snare/ Toms (Inc.Clips)	3	
Instrument	Shure	PG 81	O/H Condensor Mic	2	
Instrument	Rode	NT5	O/H Condensor Mic	4	
Instrument	Shure	SM81-LC	O/H Condensor Mic	2	
Vox / Ins	Shure	MX202	Choir mic	5	
Vocal	Shure	MX412	Gooseneck Lectern mic	6	
Vocal	Aus. Monitor	AM-G Nelec	Gooseneck Lectern mic	1	
Instrument	Sennheiser	E906		1	
Instrument	Sennheiser	E901	Kick Drum mic	1	
Instrument	Sennheiser	E904	Snare / Toms mic	3	
Instrument	Crown	PZM 6D	PZM 6D Plate mic		
Instrument	DPA pack/case cable/adpt/clips	4099	1 Bass, 2 Cello, 4 Vio, 1 Gtr, 2 Piano CLIPS	4	
DI	BSS Audio	AR-133	Active DI Box	4	
DI	Radial	Pro-AV2	Passive DI Box	2	
DI	Radial	JPC	Passive DI	1	
DI	Behringer	DI-100 Active DI Box		2	
DI	Artcessories	X-Direct Active DI Box		2	
DI	Artcessories	DTI Dual Transformer / isolator		1	
DI	Whirlwind	EDBI	Passive DI box	3	

Microphones - Radio

Item	Make	Model	Detail / Accessories	Qty
Receiver	Sennheiser	EW-300 G3	Receiver	10
Transmitter	Sennheiser	EW-300 G3	Belt Pack transmitter	10
Transmitter	Sennheiser	EW-300 G3 e835	Hand Held Microphone	10
Head worn	DPA		Wired for Sennheiser	7(1)
Lapel	Countrymen	E6	Wired for Sennheiser	5
Lapel	Shure		Clip on Lapel, Wired for Sennheiser	3

House frequencies (theatre)

546.850, 518.100, 548.775, 550.925, 556.350, 557.975, 547.550, 552.750, 553.800, 555.525

Accessories

Item	Model	Detail / Accessories	Qty
Microphone Stand	Konig & Meyer	Straight Round base (black)	6
Microphone Stand	Konig & Meyer	Short Boom (black)	8
Microphone Stand	Konig & Meyer	Tall Boom (black)	20
Speaker Stand	Konig & Meyer	Adjustable height	8

Line Patching

- Line patching to Control room 'Long frame' patch bay:

 - PS to control room = 40
 OP to control room = 24
 - Orchestra Pit to control room = 39
 - In auditorium mix position to control room = 36













Multi-core Chute runs from DSPS to Rear Auditorium

Cabling

- Audio Cable XLR 3 pin available in various quantities of:
 - 1m
 - 2m
 - 5m
 - 10m
 - 15m
 - 20m
- All Microphone cable is Black
- Multi-cores available:
 - 1 of Stage box / core 16sends 4 returns 20m length
 2 of Canare 16 channel Multi-core 10m length

Audio Notes

• FOH Speakers are fixed in position and are not moveable.













AUDIO VISUAL

Projectors

Item	Model	Detail / Accessories	QTY
NEC	PA600X	6000 Ansi Lumens Subject to Availability	1
NEC	NP3250w	4000 Ansi Lumens Subject to Availability	1
Panasonic	PT-EZ590E	5400 Ansi Lumens Subject to Availability	2
Panasonic	PT-VZ570	4800 Ansi Lumens Subject to Availability	1
Hitachi	CP- AW3005	3300 Lumens Subject to Availability	1
Panasonic	PT-RZ970B	10 000 lumens, Laser, Rigged on Balcony Rail	1

Screens

- Screen-Technics Fast fold portable projection Screen
 - o Front or rear projection
 - o 16:9 Native aspect
 - o Screen Dimensions:6087mm x 3424mm (20ft x 11ft)
- Stumpfl Fast fold portable projection Screen
 - o Screen (8ft x 12ft) 16:9 (fast fold portable)
 - o Optional Drape Kit

AV Equipment

Item	Model	Detail / Accessories	QTY
TASCAM	DV-D01U	DVD player	2
ROLAND	VR-50HD	Multi Format AV Mixer	1
KRAMER	HQV VP-728	Switcher / Scaler	1
KRAMER	VS-66HN	Splitter 6 in 6 out	1
KRAMA	VP-425	VGA to HDMI Converter	2
NEC	HXR-NX5P	Camera	2
HP	Pro Book 4530s	Laptop	2
ASUS	TP301U	Laptop	2
APPLE	MacBook Pro	Laptop	2

Cabling

- The Glasshouse has sufficient stock of:
 - o Coaxial cable
 - o RCA cable
 - o VGA Cable
 - o HDMI Cable













Mac Adapters

r	
Item	QTY
Mini DisplayPort to VGA	4
Mini DisplayPort to DVI	1
Mini DisplayPort to HDMI	1
HDMI to DVI	1
HDMI to VGA	2
30-Pin to VGA	2
Lightning to 30-pin Adapter	1
Mini DisplayPort to Ethernet	1
USB C to HDMI/VGA	2
USB C to HDMI and USB (Apple)	2

The Glasshouse can send vision and audio from the Theatre to the Ross Family Studio and both Meeting Room 1 & 2.













BACKSTAGE

Communications

- Stage Managers Console:
 - Primary Location is Prompt Side
 - Can be relocated to OP
 - Fitted with
 - Gooseneck Lamp
 - Dual Monitors (Infrared and Colour)
 - Paging master
 - Stopwatch / Clock
 - Orchestra Cue Light controller
 - Clearcom Master Station

Talk Back

- Master unit mounted in SM console (clearcom) 0
- Substation Belt packs (RS601) = 8 BTR-800 Wireless Receiver 0
- BTR Beltpacks = 4
- Beyerdynamic Headsets DT280 (Single muff) = 8
- Telex Headsets = Single ear = 3
- Talkback Patching located at:
 - Stage PS and OP
 - Fly Gallery
 - Follow-spot Positions
 - Lighting bridges
 - Audio and Lighting Control Positions
 Orchestra Pit

 - Production desk position
 - **Dressing Rooms**

Paging / Show Relay:

- Paging to dressing rooms is available via Stage managers console Show relay, Video and Audio, is distributed to all dressing rooms and Green room
- Dressing rooms and green room have individual control over show relay volume
- o Paging cannot be volume controlled

Stage Monitor (Video):

- Colour camera mounted In rear of stalls feeds to Stage Manager Console , Dressing Rooms, Green Room and Stage Door/Production
- Infra-red camera located In rear of stalls feeds to Stage Manager Console only.
- Camera located in Orchestra pit can be routed to Stage manager if required

Q-Light system

Q light system works between stage manager and Orchestra Pit only.













Dressing Rooms

Dressing Room	Capacity	Toilet	Shower	Details
Dressing Room 1	2	1	YES	On stage level.
Dressing Room 2	2	1	YES	On stage level.
Dressing Room 3	18	2	YES	One level below stage level.
Dressing Room 4	18	2	YES	One level below stage level

Laundry / Wardrobe

Laundry Facilities are located in the Basement and can be accessed Via Stairs or Goods lift. Laundry facilities contain the following items:

- Washing Machines
 - 2 of Whirlpool heavy duty domestic units
- Dryers
 - 2 of Asko T74C (butterfly drying) domestic units 1 of Asko DC 7171 Stand up drying cupboard
 - 0
- Ironing
 - 1 of Iron Board 0
 - 1 of Iron 0
- Steaming
 - o 1 of Portable 'Jiffy' Steamer
- **Clothing Racks**
 - 8 of rolling costume racks (6 in Dressing rooms)

Production Management Facilities

The following facilities are available for touring management:

- Production Desk, Can be set up in centre of Auditorium stalls. Production desk can accommodate DMX, desk lamps and Talkback.
- Stage Door is setup to accommodate a Production Office, with Internet, Phone and safe.

Greenroom

The Glasshouse Green room is located on level 1, one floor above stage. The Green room contains the following:

- Fridge / freezer
- Microwave
- Running Water Boiling Water
- Crockery
- Cutlery

The Green Room is not stocked with any consumables. Catering can be arranged through Event services prior to arrival on site.

Stage Door

Access:

Stage Door is located beside the loading dock via the forecourt (Next To Port Central Shopping Centre). Access during bump-in / out will be controlled by the Venue Supervisor. There is an Intercom that links to Venues Technical Office. Stage door is located on stage level.













ADDITIONAL INFORMATION

Orchestral

Equipment available for hire:

- 38 x music stands
- 40 x orchestra chair
- 22 x sconce lights
- 1 x Yamaha C7 7ft Grand Piano
- 1 x Yamaha Clavinova GH3 Digital Baby Grand

Rehearsal Spaces

Rehearsal spaces require booking and may incur additional hire charges

- Studio:11'000mm x 13'000mm sprung timber floor / ballet barre / mirrors (Stage Level)
- Meeting Room 1: 9860mm x 7300mm carpet on concrete floor (Level three)
- Meeting Room 2: 9860mm x 7250mm carpet on concrete floor (Level three)
- Meeting room 1 & 2 can be combined via a removable wall.

Other

- All scenery, curtains, costumes and properties must be flame retarded in accordance with the prevailing Fire Code in NSW before being brought into the Glasshouse
- All electrical equipment brought into the Glasshouse must be tested and tagged.
- Dangerous goods and Hazardous Materials brought into the Glasshouse must have prior approval from the Glasshouse, and be accompanied by a Dangerous Goods Register, Material Safety Data Sheets and all necessary safety and handling equipment.

Staff / Scheduling Requirements

- All staff must be engaged on a minimum 3 hour call
- Staff hours worked on a Sunday shall be charged at penalty rates
- Staff hours worked between 11pm and 6am Monday Saturday shall be charged at penalty rates
- Staff hours worked on Public holidays shall be charged at penalty rates
- Glasshouse staff must be provided a meal break of at least half an hour, no later than 5 hours after commencing work. Otherwise staff shall be charged at penalty rates until Meal Break is taken.













VENUE

Venue Address

32-40 Clarence Street, Port Macquarie NSW, 2444

Postal Address

PO BOX 84 Port Macquarie NSW 2444

Venue Hire Contact

Email Address Phone Number

sales@glasshouse.org.au 02 6581 8888











